

MARKED-UP COPY
OF SUBSTITUTE SPECIFICATION

WO 2005/016543 ————— PCT/EP2004/008734

————— ~~SEPARATOR COMPRISING A SPINNING DRUM WITH A DISC STACK~~

BACKGROUND AND SUMMARY

[0001] The ~~invention~~ present disclosure relates to a separator ~~according to the preamble of Claim 1~~ having a vertical axis of rotation and a drum with solids discharge openings in a single-cone or double-cone centrifugal space. The separator also includes a disk stack of super-imposed conical disks. The discs have bores forming at least one channel in the disk stack. The separator includes a distributor having a shaft concentrically surrounding a drum axis and a lower base section which expands radially. In the lower base section, one or more distributor channels are distributed in the form of bores.

[0002] It has been known for a long time to arrange disc stacks consisting of a plurality of discs situated axially above one another in the direction of the disc axis concentrically to the machine or drum axis in centrifugal drums of separators, ~~thus,~~ This is known from the field of separators with drums with a vertical axis of rotation and solids discharge openings in a pulp space outside the disc stack.

[0003] In the case of separators with a vertical axis of rotation, a feeding of the product into the centrifugal drum takes place along the drum axis through a feeding pipe and radial distributor channels connected behind the feeding pipe, ~~in which centrifugal drum the,~~ The product enters the centrifugal drum into the disc stack consisting of
[[{]]separating[[}]] discs which are generally situated closely above one another but are nevertheless spaced relative to one another in the area of the essential disc surfaces and, as a rule, are conical. At the discs, heavier solids generally accumulate on the bottom side and move to the outer circumference of the disc stack, while the liquid flows toward the interior, in, for example, a [[{]]two-phase liquid-solid separation[[}]].

[0004] ~~Particularly—but not only—for~~For the implementation of a liquid-liquid-solid separation, that is, a ~~[[{]]three phase liquid-solid separation[[}]]~~, it is also known to provide the disc stack with so-called rising channels, which are formed of bores in the discs of the disc stack situated directly or with a twist (see German Patent Document DE 100 55 398 A1) above one another.

[0005] From U.S. Patent Document US 993,791, a chamber centrifuge is known which has no solids discharge openings and in ~~the case of~~ which the diameter of the bores changes within a disc stack ~~or~~. Or, the orientation of the openings is changed from one disc to the next in that a disc holding contour sloped toward the axis of rotation is arranged, for example, at the shaft.

[0006] The discharge of the liquids generally takes place in areas radially on the inside or radially on the outside with respect to the discs of the disc stack. It is also known to construct discharge channels for the liquid phase(s) by means of bores particularly close to the inner circumference as well as close to the outer circumference of the disc stack in the disc stack (see, for example, German Patent Document DE 284640).

[0007] It is also known to equip the discs with so-called spacers in the manner of webs and/or small tips or ~~[[{]]points[[}]]~~ which, on the one hand, provide a mutual spacing of the discs and, on the other hand, influence the flow conditions in the disc stack. Spacers can be placed between the discs which preferably are separate from the ~~latter~~discs. The discs are generally held in grooves on a distributor shaft or in other disc holders.

[0008] ~~In contrast, it is an object of the invention to optimize~~The present disclosure relates to optimizing the flow conditions in the drum of a separator ~~of the above-mentioned type by means of~~ simple constructive devices.

[0009] ~~The invention solves this task by means of the object of Claim 1.~~The present disclosure further relates to a separator having a vertical axis of rotation and a drum with solids discharge openings in a single-cone or double-cone centrifugal space. The separator

also includes a disk stack of super-imposed conical disks. The discs have bores forming at least one channel in the disk stack. The separator includes a distributor having a shaft concentrically surrounding a drum axis and a lower base section which expands radially. In the lower base section, one or more distributor channels are distributed in the form of bores. A diameter of the at least one channel inside the disc stack, located above the disc which is the lowest in a flow direction, is not constant and/or is arranged to be sloped with respect to an axis of rotation of the drum. The bores of the at least one distributor channel are not radially oriented with respect to the drum axis in the drum.

[00010] ~~Advantageous embodiments are contained in the subclaims.~~ Illustrative
embodiments are described herein.

[00011] ~~According to the characterizing feature, the~~ As noted above, a diameter of the at
least one channel, within the disc stack above the lowermost disc in the a flow direction, is
not constant and/or that the at least one channel is arranged in a sloped manner with
respect to the axis of the drum and the. The bores of the at least one distributor channel do
not have a radial orientation to the drum axis in the drum.

[00012] ~~By means of each of these three measures, depending on the product~~ According
to the present disclosure, it becomes possible, particularly for example, in the case of a
centrifuge with a pulp space outside the disc stack, [()] with a piston valve arrangement or
solids discharge nozzles[()] to optimize the flow conditions in the drum. Particularly
~~advantageously, the~~ Further, according to the present disclosure, a combination of at least
~~two or even better all three of these measures~~ one or more of the above-noted features,
that is distributor and channel geometry and/or channel orientation—is, may be utilized for
optimizing the flow conditions in the centrifuge in a constructively simple manner and to
optimally adapt them to the product to be processed.

[00013] It is noted that German Patent Document DE 38 80 19 shows a centrifuge of a
different type with an inlet pipe which is not concentrically arranged.

[00014] ~~Particularly preferably, the~~ A geometry of the bores of the discs of a rising ~~the at~~
least one channel, which may be a rising channel, varies in the channel in such a manner
that, during the operation, the gaps between the discs are uniformly charged with liquid
over the entire height of the disc stack. As a result of this advantageous measure, the flow
conditions in the centrifuge are ~~particularly clearly~~ optimized. Thus, not only a simple
widening of the bores "from one disc to the next" is implemented but a flow-dependent
optimization, in the case of which the bores can be designed to be constant ~~also over~~
several discs and will then, for example, widen. In this manner, each disc separately can
have an optimal design. On the production side, this can be ~~particularly easily~~
implemented by laser cutting the bores in the metal sheet of the discs.

[00015] For example, the diameter of the channel can change in steps at a distance of
several discs or continuously from one disc to the next; ~~in particular, and~~ decrease in the
flow direction. It is ~~particularly expedient~~ for the diameter to decrease, for example,
continuously, in the flow direction.

[00016] The bores ~~per se~~ may have an arbitrary shape. ~~The~~ An optimal shape is
determined by a person skilled in the art by tests as a function of the product. Thus, the
bores may have a polygonal or round or curved shape, ~~specifically,~~ in any alignment.

[00017] ~~According to another advantageous variant~~ In an illustrative embodiment, each
channel ~~consists of~~ includes several bores which, in turn, ~~particularly advantageously~~ may
also form a perforated pattern ~~[[-]]~~ for example, distributed on the circumference on a
circle or an ellipse ~~[[-]]~~ in the discs.

[00018] It is ~~also conceivable~~ within the scope of the present disclosure that the at least one
~~sloped channel, which may be sloped,~~ extends in a curved manner with respect to the drum
axis in the disc stack.

[00019] In ~~this case~~ such an embodiment, the ~~channel/channels~~ at least one channel may
~~particularly preferably~~ comprise a rising channel for feeding the product into the disc stack

and/or, ~~particularly advantageously,~~ at least one discharge channel for discharging the liquid phase from the disc stack. The optimized design of rising and discharge channels also contributes to improving the flow conditions.

[00020] ~~Particularly preferably, one~~ One of the discharge channels ~~respectively~~ for discharging various liquid phases is constructed close to the inner circumference or close to the outer circumference of the disc stack and/or is constructed inside the disc stack. The flow direction extends in the direction of the liquid discharges of the drum, with the vertical orientation generally in the upward direction.

[00021] ~~By means of one or more of the above-described measures~~ Based upon the present disclosure, it becomes possible ~~by means of simple experiments~~ to optimize the further development of the channels of a separator with a vertical axis of rotation as a function of the product and the machine in order to improve the parallel connection of the discs of the disc stack and to optimize the flow conditions. That is done in order to, for example, compensate separating zone displacements because of pressure differences in the disc stack, for example a ~~[[{]]~~radial position~~[[{]]~~ and to reduce instabilities in the disc stack, for example, [[{]]in the circumferential direction~~[[{]]~~.

[00022] ~~The invention is expediently supplemented by the above-mentioned measure,~~ which can also be considered independently, ~~of~~ present disclosure also includes providing a distributor with at least one distributor channel constructed as a bore in a distributor base, ~~which~~. Such a distributor channel is not oriented radially in the drum, which, in turn, optimizes the flow conditions in a simple manner as a function of the product.

[00023] ~~In many cases, it is, for example, advantageous for~~ According to the present disclosure, the distributor channels ~~to preferably may~~ be oriented in a sloped manner against the rotating direction of the drum or under certain circumstances in the rotating direction of the drum.

[00024] The distributor channels, which are formed by bores relative to the radial line through the drum axis in a radially interior bore section against the rotating direction of the drum, advantageously ~~are~~ may be oriented to be sloped in a lagging manner.

[00025] As a result of ~~this measure~~ that orientation, the flow conditions are further optimized ~~particularly also~~ in combination with the measure that the distributor channels lead in a further bore section into the drum, which bore section is oriented upwards in the drum and leads out directly below a rising channel of the disc stack into the drum. In addition, a more careful acceleration and an optimal entry of the centrifugal material into the rising channels is ensured.

[00026] ~~In this case, the~~ The distributor channels may have an expanding round or a slot-type outlet which extends tangentially in or against the rotating direction of the drum and/or is directed upward in the drum.

[00027] ~~In the following, the invention will be explained in detail by means of embodiments with reference to the drawing. Other aspects of the present disclosure will become apparent from the following descriptions when considered in conjunction with the accompanying drawings.~~

BRIEF DESCRIPTION OF THE DRAWINGS

[00028] Figure 1 is a top view of a partial area of a known disc for disc-type centrifuges having a vertical axis of rotation.

~~8~~**[00029]** Figures 1-2 to 8 are top views respectively of a partial area of embodiments of different discs for disc-type separators or centrifuges with having a vertical axis of rotation[[;]], according to the present disclosure.

~~9~~**[00030]** Figure 9 is a sectional view of a schematically illustrated separator and of having two distributor channels; and, according to the present disclosure.

~~10~~**[00031]** Figure 10 is a top view of a distributor for a the separator of the type of Figure 7.

DETAILED DESCRIPTION

~~14~~[00032] _____ Figure 1 ~~is shows~~ a top view of a partial area of a known disc 1 of a disc stack for a separator ~~(otherwise not shown here)~~.

~~12~~[00033] _____ According to Figure 1, the discs 1 each have a disc bore 2, ~~the~~. The bores 2 or holes of the discs 1, in cooperation with several discs 1 arranged above one another, ~~forming form~~ a rising channel 3 which is situated radially in ~~the an~~ area of ~~the a~~ separating zone T between a lighter and a heavier liquid phase. In an area 4, ~~the a~~ discharge of a light liquid phase takes place radially on ~~the an~~ inside with respect to the discs 1, and ~~the a~~ discharge of a heavier liquid phase takes place in an area 5 radially outside the disc 1. ~~The solids~~ Solids exit ~~the a~~ disc stack 26 toward ~~the an~~ outside (not shown here) and can be discharged there in a known manner, for example, through nozzles or a piston valve arrangement from ~~the a~~ centrifugal drum.

~~13~~[00034] _____ The disc stack 26 or the individual discs 1 are pushed onto ~~the a~~ distributor shaft 16 which ~~is equipped includes~~, on its outer circumference ~~with~~, a plurality of webs 17 directed radially from the shaft 16 to ~~the an~~ outside, which webs 17 protrude beyond the an inner circumference I of the discs 1 and thereby non-rotatably secure the discs 1 on the distributor shaft 16 relative to the ~~latter~~ shaft 16.

~~14~~[00035] _____ As a radial extension of the webs 17, ~~also radially directed~~ spacers ~~(lugs) or lugs~~ 18 are arranged between the discs 1, which spacers 18 divide the discs 1 completely into segments 19 with an opening angle α , in which one bisecting line W ~~respectively is~~ situated.

~~15~~[00036] _____ The area 4 for discharging the light phase is formed by grooves 20 in the outer circumference of the distributor shaft 16 between the webs 17, which grooves 20 are placed symmetrically with respect to the bisecting lines W in the distributor shaft 16.

~~16~~[00037] _____ According to Figure 2, the rising channel 3 has a cross-section which is not constant; ~~that~~. That is, ~~the a~~ diameter of the bores 2 of the ~~disks discs~~ 1 of the disc

~~stack~~disc stack 26, which form the rising channel 3, is not constant. ~~4-~~The diameter changes over ~~the an~~ entire height of the ~~disc stack~~disc stack 26 ~~(here, and~~ it is reduced continuously along the entire height of the ~~disc stack~~disc stack 26 in the a flow direction~~[[]]~~ F (see Figure 9).

~~17~~[00038] It is noted that it is known from British Patent Document GB 264,777 to provide the lowermost disc with a different hole or bore arrangement than the upper discs in order to cover a portion of the discs and be able to thereby radially displace the rising channel by exchanging the lowermost disc.

~~18~~[00039] The diameter of the bores ~~bore~~ 2, according to ~~as shown in~~ Figure 2 ~~in the case of,~~ for a drum with a vertical axis of rotation, preferably continuously decreases in the an upward direction (indicated by a broken line), so that the diameter of the rising channel 3 is also reduced in the upward direction.

~~19~~[00040] In addition, the rising channel 3 ~~according to,~~ as shown in Figure 2, is not situated parallel to the a drum axis A ~~(M which is perpendicular to the a plane of the figure[[]])~~. As a result, the bores 2 of discs 1 situated above one another are no longer aligned completely but only in sections, so that the rising channel 3 may, for example, extend in the upward direction radially from the outside farther toward the inside and/or in or against the a rotating direction in the a circumferential direction and may therefore have a twist.

~~10~~[00041] According to Figure 2, the groove 20 in the distributor shaft 16 for forming the a discharge channel or discharge area 4 is not symmetrically aligned with respect to the bisecting line W of each disc segment 19 but is asymmetrically laterally offset. This can also optimize the flow conditions in the ~~disc stack~~disc stack 26.

~~14~~[00042] According to Figures 3 to 6, the ~~5,~~ discharge channels 6, 7 are constructed directly in the ~~disc stack~~disc stack 26; ~~that.~~ That is, a first discharge channel 6 for a light liquid phase is ~~in each case~~ constructed radially outside the inner circumference I of the discs 1

in the ~~disc stack~~disc stack 26, and a second discharge channel 7 for a heavier liquid phase is constructed radially inside the outer circumference A of the discs 1. These channels 6, 7 also may be aligned not only symmetrically but also asymmetrically with respect to the bisecting line W of each disc segment 19. This also applies to the rising channels 23 for the product feed.

12][00043] _____ The discharge channels 6, 7 are formed analogously to the rising channels 3 by bores 8, 9 in the discs 1 situated above one another, which bores 8, 9 are situated close to the inner I or outer A circumference of the discs 1. The discharge channels 6, 7 may again have a diameter which is not constant and/or may not be situated directly above one another but offset with respect to one another relative to the a drum axis M. To this extent, all of the arrangements of the bores 2 for the rising channels 3 mentioned above or below can be analogously utilized also when further developing the bores 8, 9 for the discharge channels 6, 7.

13][00044] _____ According to Figure 3, the bores 8 of the inner discharge channel 6 for the light liquid phase and/or the bores 9 of the discharge channel 7 for the heavier phase and/or the bores 2 of the rising channel 3 may ~~in each case again consist of~~include several bores 2, 8, 9 in the a manner of a multiple perforation 10. In this case, the individual bores can be arranged, for example, in a circle 12, ~~particularly~~ in a radially oriented straight line or in a curve oriented in the circumferential direction or a straight line 13. The curves or straight lines may be arbitrarily oriented in an angular and/or offset manner with respect to the bisecting line W of the segment 19 or to other radial lines through the drum axis A-M of the centrifuge depending on the application.

14][00045] _____ ~~It was found that the~~According to the present disclosure, a division of the product flow into many small channels represents an improvement with respect to the uniform charging of the ~~disc stack~~disc stack 26s and optimizes the flow conditions in the ~~disc stack~~disc stack 26.

~~15~~[00046] The individual bores 2, 8, 9 may have any geometry; ~~thus~~. Thus, a circular shape or a polygonal shape, for example, a triangular or square shape, as shown in Figure 4 or a curved shape, as shown in Figure 5. The polygon or the other geometrical shapes can be oriented at any angle with respect to the bisecting line W of the angle.

~~16~~[00047] It is ~~particularly advantageous~~ to mutually adapt the geometry of the bores 2, 8, 9 of a rising channel 3 such that ~~the gaps between the discs 1~~ are uniformly charged with liquid over the entire height of the ~~disc stack~~ disc stack 26 or the rising channel 3. This can be achieved by tests and/or theoretical considerations, such as computer simulations.

~~17~~[00048] Figures 6 to 8 illustrate that, by ~~means of an optimized further development of the distributor, it also and/or optionally becomes possible to further optimize the flow conditions in the drum 21 (see Figure 9) as well as at the and in the disc stack~~ disc stack 26.

~~18~~[00049] Here, ~~the preferably A one-piece distributor 22 (see Figure 10) is provided with distributor channels 14 which are not radially oriented~~. The channels 14 are constructed as a bore (see Figure 9) and, first (Figure 9) extend in a first bore section in the drum 21 in a sloped manner from ~~the an~~ inside to ~~the an~~ outside in ~~the a~~ downward direction and end in a bore section which is constructed as ~~a preferably an~~ expanding or geometrically changing distributor outlet 15a. This distributor outlet 15a is directed upward in the drum 21 and preferably leads directly below one of the rising channels 3. Its outlet area may have a circular or, for example, slot-type shape. ~~The slot~~ Slot-type distributor outlets 15b (see Figure 7) from the bores of the distributor channels 14 (Figure 6) may then, in turn, extend relative to ~~the a~~ remaining distributor channel preferably tangentially to ~~the radial line R in the rotating direction r of drum 22 (Figure 7) or against (Figure 8) the rotating direction r of the drum 22, or may advance or lag.~~

~~19~~[00050] ~~In this manner, it~~ It thus becomes possible to optimize the flowing of the product into the drum 22 as well as into the ~~disc stack~~ disc stack 26 in a very targeted manner while ~~the a~~ feeding bore cross-section is optimized~~[[,]]~~. This is in order to achieve an improved separation of the particles and, if required, improve ~~the a~~ parallel connection of the discs 1.

~~10~~[00051] Figure 9 is a cross-sectional view of a schematically illustrated self-discharging separator having a drum 21 with a vertical axis of rotation D, which has a distributor 22. A feeding pipe, which is not shown, leads from above into the distributor 22. The distributor 22 has the upper distributor shaft 16, which is oriented concentrically with respect to the axis of rotation, ~~as well as several D~~. The distributor 22 includes distributor channels 14 which are constructed as bores and each lead into one of the distributor outlets 15 (as shown in Figure 9) or 15a,b,c (as shown in Figure 10). A piston valve 23 is used for the opening and closing of solids discharge openings 24. The liquid discharge from the drum 24 ~~preferably takes place by means of grippers or centripetal pumps which are also not shown here~~ (not shown).

~~11~~[00052] Figure 10 is a corresponding top view of the distributor 22 with the distributor shaft 16 and the lower, radially expanding, almost disc-type base section 25, ~~which~~. Section 25 is penetrated by the, for example, three distributor channels 14, shown here by broken lines, and leading into the distributor outlets 15a,b,c.

~~12~~[00053] ~~The straight~~ Straight bores, which form the distributor channels 14 in the ~~particularly preferably one-piece distributor 22, in this case,~~ are not arranged radially but relative to the radial line ~~r~~ R through the drum axis M (~~which here is congruent with the axis of rotation D in the drawing~~) in a lagging manner with respect to the rotating direction r, which permits a ~~particularly careful~~ inflow of the centrifugal material.

~~13~~[00054] ~~This is again preferably accompanied by the measure of designing the~~ The holes of the rising channel 14 are designed not to be constant over the height of the ~~disc stack~~ disc stack 26 ~~but to design them~~. The holes are designed in an optimized manner

with respect to the flow conditions to not be constant-~~(variable)~~, that is, to be variable.
The An angle β between the distributor channels 14 and the radial line R, which extends through the a starting area of the distributor channel ~~[[ϵ]]14[[\rangle]]~~ at the an inner circumference of the distributor 22, preferably amounts to between 15 and 85°, particularly between 25° and 65°, in order to achieve a ~~particularly~~ careful inflow of the centrifugal material into the drum 21.

[00055] The distributor outlets 15a,b,c may have various geometries which are also adapted to the rising channels 3 and which ~~again~~ may be oriented to be lagging ~~[[ϵ]]15b[[\rangle]]~~, advancing ~~[[ϵ]]15c[[\rangle]]~~ or "neutral" ~~[[ϵ]]15a[[\rangle]]~~ relative to the a lagging distributor arm (see also Figure 10).

[00056] Although the present disclosure has been described and illustrated in detail, it is to be clearly understood that this is done by way of illustration and example only and is not to be taken by way of limitation. The scope of the present disclosure is to be limited only by the terms of the appended claims.

| | |
|---------------------------|-------|
| Reference Symbols | |
| Disc | 1 |
| bore | 2 |
| rising channel | 3 |
| area | 4 |
| area | 5 |
| discharge channel | 6 |
| discharge channel | 7 |
| bores | 8,9 |
| multiple perforation | 10 |
| circle | 12 |
| straight line | 13 |
| distributor channel | 14 |
| distributor outlet | 15a,b |
| distributor shaft | 16 |
| webs | 17 |
| spacers (lugs) | 18 |
| segments | 19 |
| grooves | 20 |
| drum | 21 |
| distributor | 22 |
| piston valve | 23 |
| solids discharge openings | 24 |
| expanding base section | 25 |
| inner circumference | 1 |
| outer circumference | A |

| | |
|-------------------------|----------|
| separating zone | T |
| opening angle | α |
| bisecting line of angle | W |
| radial line | R |
| rotating direction | F |
| axis of rotation | D |